

2.0MP IP Vandal Dome Camera



Features:

- 1/2.9" Sony IMX323 CMOS sensor
- Full HD resolution 1920 x 1080P
- Ultra low illumination 0.01Lux
- Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR, IR-CUT
- D-WDR, Motion Detection, Privacy Mask, Mirror
- RTSP and Onvif 2.6 compatible
- H.265/H.264 dual-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- Optional customization Lens/Audio/Alarm/Storage/POE, etc.
- Lightning protection 4000V
- Strong water-proof housing, IP65
- Array / SMD IR Leds, IR distance optional
- Vari-focal 2.8-12mm lens

Installation:

- To prevent shock or damage to the waterproof body, tighten all screws and cover.
- Adjust the sunshield to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol
- Do not install camera where vibration is present.
- Do not install camera where temperature is above 50°C or below -20°C.
- Do not expose power or video connection to moisture or water
- If camera is not functioning properly, please power off and contact the manufacturer.

Note: Non-regulated power supply may cause damage to camera.

Technical Specifications:

Model	IV-NT6E32B-B
Camera	
Image Sensor	1/2.9" Sony IMX323 CMOS
Effective Pixels	1984(H)×1105 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
BLC / HLC	Support
DNR	2D/3D DNR
Other	Motion Detection, Privacy Mask, Mirror, Flip
Encode	
Embedded Solution	Hi3516C v300+Sony IMX323
Video Standard	H.264/H.265
Video Resolution	Main stream: 1080P/720P@30fps
	Sub stream: VGA/360P/CIF@30fps, etc.
Video Bitrates	500Kbps - 6Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a/AAC
IR Led	
IR Led	24pcs SMD Array Leds
IR Distance	30-40m
Lens	
Focal length	2.8-12mm lens
Optional Function	
POE, Audio, etc.	
Network Services	
Protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/NFS
P2P	Yes
Web	IE , Firefox, etc.
Media	CMS, Android, IOS
ONVIF	2.6 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC ± 10%
Power Consumption	< 5 W
Operating Temp.	-30℃-(+60)℃, 10%-90%RH