

2MP Motorized Eyeball IR IP Camera



Features:

- 18 pcs SMD Array IR LEDs, IR distance 30-40 meters
- 1/2.9" Sony IMX323 CMOS sensor
- UHD resolution 1920 x 1080P
- Ultra low illumination 0.01Lux
- Day/Night (ICR), AWB, 2D/3D-DNR, IR-CUT
- D-WDR, Motion Detection, Privacy Mask, Mirror, rotate
- RTSP and Onvif 2.6 compatible
- H.265/H.264 dual-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- Optional Built-in POE, lens
- Lightning protection 4000V
- Strong Vandal-proof housing, IP66
- 18 pcs SMD Array IR LEDs, IR distance 30-40 meters
- 2.8- 12 mm AF lens

Installation:

- To prevent shock or damage to the waterproof body, tighten all screws and cover.
- Adjust the sunshield to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol
- Do not install camera where vibration is present.
- Do not install camera where temperature is above 50°C or below -20°C.
- Do not expose power or video connection to moisture or water
- If camera is not functioning properly, please power off and contact the manufacturer.

Technical Specifications:

Model	IV-NT5732M
Camera	
Image Sensor	1/2.9" 2.1MP IMX323 CMOS
Effective Pixels	1984(H)×1105 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
BLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate
Encode	
Embedded Solution	Hi3516D
Video Standard	H.264/H.265
Video Resolution	Main Stream:30fps@1080P/720P
	Sub stream: VGA/360P@30fps, etc.
Video Bitrates	32Kbps - 8Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a/AAC
OSD Overlay	Title and Time overlay
IR Led	
IR Led	18 pcs SMD IR Leds
IR Distance	30-40 M
Lens	
Focal length	2.8 -12 mm AF lens
Zoom	4x optical zoom
Network Services	
Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
P2P Cloud	Yes
Web	IE , Firefox esr.
Media	CMS, Android, IOS
ONVIF	2.6 compatible
General	
Network Port	1-RJ45, 100Mbps, POE
Power	POE , (AC 24V optional)
Power Consumption	< 8 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH