

## 2.1 MP 1080P 4-IN-1 Auto Focus IR Vandal Dome Camera



### Features:

- Dual output AHD/CVI/TVI/ and CVBS
- Full HD resolution 1920 x 1080P
- Ultra low illumination 0.01Lux
- Up to 300M long distance and high speed real time monitoring
- OSD menu control up the coaxial cable (UTC)
- Low light and high dynamic range
- Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR
- D-WDR, Slow-Shutter, Smart IR, Sens up, Defog
- Motion Detection, Privacy Mask, Mirror, Digital Zoom
- Lightning protection
- Strong water-proof housing, IP66
- 24pcs Array IR Leds, IR distance 35-40 meters
- 2.8 – 12 mm AF lens

### Installation:

- To prevent shock or damage to the waterproof body, tighten all screws and cover.
- Adjust the sunshield to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol
- Do not install camera where vibration is present.
- Do not install camera where temperature is above 50°C or below -20°C.
- Do not expose power or video connection to moisture or water
- If camera is not functioning properly, please power off and contact the manufacturer.

### Technical Specifications:

<b>Model</b>	<b>IV-HDR6E22AV-E</b>
<b>Camera</b>	
Image Sensor	1/3" 2.1 Mega pixels Sony CMOS
Chipset	EN771+IMX323
Effective Pixels	1985(H)×1105 (V)
Video Resolution	1080P@25/30fps
Electronic Shutter	AUTO, 1/25 - 1/50,000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Video System	PAL/NTSC
Video Output	1 channel, AHD/CVI/TVI adjustable ; 1 channel, CVBS
Day/Night	Auto/Color/(B/W)/EXT
WDR	Double scan Digital WDR
White Balance	AWB/ATW/Indoor/Outdoor/Manual
AGC/BLC/HLC	Support
DNR	2D 3D NR
OSD Menu	Multiple languages OSD menu control up the coaxial cable (UTC)
Other	Motion Detection, Privacy Mask, Mirror, Flip, ACE, Defog, Digital Zoom
<b>IR Led</b>	
IR Led	24pcs SMD Array IR Leds
IR Distance	35-40 M
<b>Lens</b>	
Focal length	2.8 -12 mm AF lens
<b>General</b>	
Power Supply	12 VDC ± 10%
Power Consumption	< 8 W
Operating Temp.	-20°C-(+60)°C, 10%-90%RH