

Full HD 1080P Starlight IP Mini Bullet Camera



Features:

- 1/2.8" Sony IMX307 CMOS sensor
- Full HD resolution 1920 x 1080P
- Ultra low illumination 0.001Lux(Color)
- Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR, IR-CUT
- D-WDR, Motion Detection, Privacy Mask, Mirror, Rotate.
- H.264 /H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- Optional customization Lens/Audio/POE, etc.
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 3.6mm F1.0 lens

Installation:

- To prevent shock or damage to the waterproof body, tighten all screws and cover.
- Adjust the sunshield to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol
- Do not install camera where vibration is present.
- Do not install camera where temperature is above 50°C or below -20°C.
- Do not expose power or video connection to moisture or water
- If camera is not functioning properly, please power off and contact the manufacturer.

Note: Non-regulated power supply may cause damage to camera.

Technical Specifications:

Model	IV-NT9432S
Camera	
Image Sensor	1/2.8" Sony IMX307 CMOS
Effective Pixels	1945(H)×1097 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.001Lux (Color)
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
AGC/BLC	Support
DNR	2D/3D DNR
Other	Motion Detection, Privacy Mask, Mirror, Flip
Encode	
Video Standard	H.264/H.265
Video Resolution	Main stream: 1080P/720P@1-20/30fps Sub stream: 640*480,640*360@1-30fps
Video Bitrates	32Kbps - 5Mbps, VBR/CBR
Audio Standard	G.711/AAC
OSD Overlay	Title and Time overlay
IR Led	
IR Led	No
IR Distance	No
Lens	
Focal length	3.6mm
Optional Function	
POE, Audio, etc.	
Network Services	
Protocol	HTTP/RTSP/FTP/PPPOE/DHCP/DDNS/NTP/ONVIF/P2P/UPNP, etc.
P2P	Yes
Web	IE 6.0+
Media	CMS, Android, IOS, Windows Mobile
ONVIF	2.4 compatible
General	
Network Port	100Mbps, POE optional
Power Supply	12 VDC ± 10%
Power Consumption	< 5 W
Operating Temp.	-30℃-(+60)℃, 10%-90%RH